

# LIFTING EQUIPMENT

## SERVICE JACKS

**HEIN-WERNER  
AUTOMOTIVE**

### HWAHW93642 2 Ton Heavy Duty Service Jack

- One-piece handle
- Flanged side plates increase strength
- In-line pump provides efficient pumping operation
- Full swivel rear casters for easy positioning
- Sealed hydraulic pump for durability
- Pressure relief valve prevents overloading
- Cast iron lift arm for heavy duty loads
- U-joint release mechanism for precise load control



HWAHW93642

**HEIN-WERNER  
AUTOMOTIVE**

### HWAHW93657 4 Ton Manual Hydraulic Service Jack

- Handle adjusts to three pumping positions
- Extra long chassis reaches under low overhangs
- "T" handle permits easier maneuvering
- Automatic valve prevents overloading
- Low height 5-1/4", High height 26"



HWAHW93652

**HEIN-WERNER  
AUTOMOTIVE**

### HWAHW93652 3 Ton SUV Service Jack

- Heavy duty frame for rugged applications
- Longer chassis ideal for truck's & SUV's
- One piece "T" handle for easy positioning and less lifting effort
- Foam handle pad protects the vehicle
- U-joint release mechanism for precise load control

**HEIN-WERNER  
AUTOMOTIVE**

### HWAHW93660 10 Ton Manual Hydraulic Service Jack

- Chassis and handle reach under long, low overhangs
- Large handle knob provides fine load release control
- Handle adjusts to three pumping positions
- Forged steel hydraulic unit base is sealed for long life and reliability
- Automatic valve prevents overloading
- Low height 5-7/8", High height 26"



HWAHW93660

**HEIN-WERNER  
AUTOMOTIVE**

### HWAHW93662 10 Ton Air/Manual Hydraulic Service Jack

- Operates manually or with air.
- Patented "Speed Pak" eliminates handle pumping, saves lift times — the air does the work.
- Loads moved into position hydraulically. Air hose may be disconnected for other uses.



HWAHW93662

**OTC**

### OTC1739 Two-Speed, 3 Ton Jack

- Padded jack handle is angled back, allowing you to easily extend the jack without banging the handle against the bumper.
- At load in just one stroke.
- Positioning under air dams is easy, thanks to the 48" long handle and the jack's 30-1/2" chassis length.
- Specially designed square saddle provides a safe and secure lifting platform.
- The largest power unit in its class, with a massive, sealed cylinder that prevents contamination from dirt and moisture, ensuring a long life.
- Conforms to ANSI PALD Part 10

Specification:  
Capacity: 3 Tons  
Lifting range: 4" to 24-1/2"  
Saddle square: 6-1/2"  
Overall reach: 27"  
Frame height: 7"  
Handle length: 48"  
Floor space: 30-1/2" x 15-3/4"



OTC1739

**P Performance  
Tool**

### WLMW1617 3 Ton Service Jack

- 6,000 lb. capacity
- Max. height 21-1/4"
- Steel lifting saddle with 360° swivel



WLMW1617

**OTC**

### OTC1505B — 5 Ton Service Jack OTC1510B — 10 Ton Service Jack

- A built-in safety overload prevents using the jack beyond its rated capacity.
- Convenient foot pedal speeds the lifting operation. Handle lock and release control are located on top of the handle. Handle can be locked into any position from vertical to horizontal.
- Spring-loaded 40" handle.

Specifications:	OTC1505B	OTC1510B
Capacity:	5 Ton	10 Ton
Lifting Range:	6" to 22"	5-3/4" to 22"
Saddle Diameter:	5-1/8"	6"
Overall Reach:	47"	51"
Frame Height:	7-3/4"	9-3/4"
Handle Length:	43"	43-1/4"
Floor Space:	14-3/4" to 56"	18" to 60"
Weight:	232 lbs.	412 lbs.



OTC1505B  
OTC1510B

## AIR JACKS

**herkules**



HERAJ3



HERAJ2



**herkules**

### HERAJ2, HERAJ3 AJ-2 & AJ-3 Air Jacks

Use wherever jacks are needed including frame machines, wheel removal, brake and tire work.

- 6-1/2" to 23-3/16" positions with 4500 lbs. capacity