

LIFTING EQUIPMENT

FLOOR JACKS

WLMW1620



WLMW1620
1-1/2 Ton Aluminum Floor Jack

- 3,000 lb. capacity
- 3-1/2" to 17-1/2" Lift Range
- Rubber saddle prevents marring, rotates 360°
- 37 lb. GSW

WLMW1630



WLMW1630
1-1/2 Ton Rapid Lift Aluminum Floor Jack

- 3-5/8" to 17-1/2" Lift range
- 47-3/4" Cushion grip handle
- 3 Pumps to maximum height
- 360° Swivel saddle with rubber cushion

WLMW1614



WLMW1614
2 Ton Floor Jack

- 4,000 lb. capacity
- Maximum height 15"
- Swivel casters for easy positioning



WLMW1618
2-1/2 Ton High Lift Floor Jack

- Designed for SUVs and other high ground clearance vehicles
- 5-3/8" to 21" Lift range
- 5,000 lb. capacity
- Heavy duty construction

WLMW1618



WLMW1612



WLMW1612
2-1/2 Ton Commercial Floor Jack

- 5,000 lb. capacity
- Maximum height 19-1/4"
- Heavy duty construction
- 84 lb. GSW



WLMW1616
3 Ton Rapid Lift Floor Jack

- 6,000 lb. capacity
- 4-5/8" to 19-3/4" Lift Range
- Rapid lift feature allows you to quickly raise jack into position under the vehicle

WLMW1616



AXLE JACKS



OTC5012A
25 Ton Capacity Under-Axle Hydraulic Jack and Accessories

- Self-retracting, air-driven ram uses standard shop air. Release valve automatically applies air to retract ram.
- Low 8" minimum working height enables jack to get under any truck in the shop.
- Positioning jack is easy, even under vehicles with set-back axles, thanks to a 53" handle that locks into any of three positions, from vertical to horizontal.
- Maximum lift is 21" when used with the 3" lifting extension (included).
- Covered by the OTC Lifetime Marathon Warranty®. Exceeds ANSI PALD standards.
- Weight: 117 lbs.
- Includes No. 220972 Lifting extension. (3" long and a 1" diameter. Wt., 3 lbs., 4 oz.)

Specifications:

Lifting range:	8" min. height
with screw retracted:	13-1/8" max. height
Lifting range:	12-7/8" min. height
with screw extended:	18" max. height
Cylinder stroke:	5-1/8"
Extended screw Length:	4-7/8"
PSI range:	100-200



OTC5012A



OTC1788A
22 Ton Capacity Under-Axle Jack

- Self-retracting, spring return feature.
- Long 50" T-handle lets you easily position jack under vehicles with long overhangs.
- One pull of the handle activates the self-retracting 22 ton capacity ram without having to crawl underneath the vehicle.
- Jack has large rubber-tired wheels.
- Lifting range:
Screw Extd. – 8" min./17" max. ht. w/adpt.
Screw Retd. – 8" min./12-1/2" max. ht.
- Cylinder stroke, 4-3/4"; extended screw length, 5"; PSI range, 90-145.
- Weight: 102 lbs.



OTC1788A



HWAHW93733
20 Ton Air Operated Hydraulic Service Jack Low Height Pick-Up

- Powerful, compact, portable design
- Large 8" rubber wheels for easy maneuverability
- Low height allows lifting from axles or suspension
- Automatic valve prevents overloading
- Rapid two-speed air-hydraulic action quickly advances ram to load
- Chrome plated plunger for extended jack life
- Built-in overload valve
- Low height 9", High height 19-3/4"



HWAHW93733