

BODY CLAMPS



MOC0045

MOC0045

Angle Bite™ Clamp

The Angle Bite™ Clamp is a self-cleaning, self-tightening clamp with a gator tooth design and a 45-degree head for those hard-to-pull areas, such as the Mercedes 107 front chassis rail. Drop-forged wedge for extra durability and long life. Gripping Surface: 2-1/4" wide (57 mm) Overall Length: 9-1/4" (235 mm) Weight: 6 lbs (2.72 kg) Capacity: 5 tons (4,536 kg)



MOC0054

MOC0054

Mini Spring™ Clamp

Spring loaded for easy opening. Includes Oval Loop for use with Slip Hook for easy hook-up. For light sheet metal in those tight places. Cross-hatch tooth design for an aggressive bite. Clamp has raised "ears" to hold bolts stationary, for easy, one-handed tightening. Gripping Surface: 1-1/2" (39 mm), 3/4" deep (19 mm) Overall Length: 6" (152 mm) Weight: 3 lbs (1.36 kg) Capacity: 3 tons (2,722 kg)



MOC0205

MOC0205

Dyna-Mo™ C Clamp

New generation of Mo-Clamps. Self-tightening. Great for getting over lips or edges. Drop-forged round wedge to keep the twist out of chain, aggressive cross-hatch tooth design, spring-loaded for easy opening. Gripping Surface: 1-1/4" wide (32 mm), 1/2" deep (13 mm) Overall Length: 7" (178 mm) Weight: 2 lbs (.91 kg) Capacity: 3 tons (2,722 kg)



MOC0305

MOC0305

Dyna-Mo™ Jr. Clamp

New generation of Mo-Clamps. Self-tightening. Thin-edged nose for getting into hard-to-reach places. Drop-forged round wedge to keep twist out of chain, aggressive cross-hatch tooth design, spring loaded for easy opening. Gripping Surface: 1-1/4" wide (32 mm), 1" deep (25 mm) Overall Length: 7" (178 mm) Weight: 2 lbs (.91 kg) Capacity: 3 tons (2,722 kg)



MOC0405

MOC0405

Dyna-Mo™ W Clamp

New generation of Mo-Clamps. Self-Tightening. Wider tooth surface to grab more thin metal without tearing. Drop-forged round wedge to keep twist out of chain and aggressive cross-hatch tooth design. Gripping Surface: 2-1/4" wide (57 mm), 1-3/4" deep (45 mm) Overall Length: 7" (178 mm) Weight: 3 lbs (1.36 kg) Capacity: 3 tons (2,722 kg)



MOC0805

MOC0805

Tac-N-Pull™ Pull Plate Kit

For hard-to-hold pulls. Tack weld one of the reusable plates. Attach clamp and pull. Break tack weld with a grinding cut-off wheel or cutting torch. The Pull Plate Kit includes: Ten (10) #0801 1" Pull Plates, Five (5) #0802 1" Pull Plates, and Five (5) of #0803 3" Pull Plates. For use with the #0800 Tac-N-Pull™ Clamp. (Clamp not included in kit.)



COLLISION REPAIR TOOLS & ACCESSORIES



Innovative autobody tools and equipment



MOC2450

MOC2450

Boltless Strut Tower Puller

Easy, fast, reliable method for pulling strut towers. Developed for strut towers without bolts, to correct chassis dimensions to factory specifications. Strut tower removal is necessary. Overall Length: 5" (127 mm) Weight: 8 lbs (3.63 kg) Capacity: 3 tons (2,722 kg)



MOC4058

MOC4058

MAC II™ Multi-Angle Clamp

New style features cross-hatch tooth pattern which holds well with less distortion of metal. Larger pull plate is adjustable and reversible for more multi-angle pulls. Clamp has "bolt stoppers" to hold bolts stationary for easy tightening. Gripping Surface: 3" wide (95 mm), 5/8" deep (16 mm) Overall Length: 9" (229 mm) Weight: 8 lbs (3.63 kg) Capacity: 4 tons (3,629 kg)



MOC5616

MOC5616

Door Post Puller/Twister

Designed to put a twist in your pull with its V-shaped gusset. There are three positions from which to pull. For use on bolt-type hinge pillars. Overall Length: 5" (133mm) Slots: 1/2" x 1" (12mm x 39mm) Weight: 2 lbs (.91kg) Capacity: 2 tons (1,814kg)

STK60002

Iron Hand

The Iron Hand easily pulls closed end rails using the existing isolator shock absorber. The wide flange tool also realigns floor jams, rocker panels and pillars without additional damage to the vehicle.

- Iron Hand installs quickly on shock absorbers for pulls in any direction (read instructions carefully).
- Iron Hand adjusts to pull most rocker panels, door jams and pillars.



STK20080

STK20081

BigBite Radius Pull Clamp with Side Pull Ring

- 35 heat treated teeth to grip pinchweld
- Allows side pulls on corners of door openings
- In-line pulls with optional linear pull ring
- Also works in other hard-to-pull places for multidirectional pulls
- Reverse Pulls

STK20080 — BigBite Radius Pull Clamp with Side Pull Ring

STK20081 — Optional Linear Pull Ring

BODY CLAMPS



Hi-Tac Clamp



M200

M200

Hi-Tac Clamp for Imports

M200 is ITS tested and certified for 5 ton pulling capacity. Comes with M50 L-shaped adapters. Dimensions 2-1/2" x 4-1/2"

Focused for repairing Asian models: Toyota, Honda, Mazda, Lexus, Nissan, Subaru, Mitsubishi and more, as well as European models: Volvo, BMW, Mercedes and more.



M600

M600

Hi-Tac Clamp for Frame Rail Pulling

The M600 replaces over (54) other pulling clamps. Also the M600 is ITS tested and certified for 7 ton pulling capacity. Comes with M60 L-shaped adapters. The M600 is used 95% for frame rail pulling attachment. Dimensions 4-1/2" x 6-1/2"

This clamp is designed specifically for a wide range of body styles like SUVs, cars or trucks, including General Motors, Ford and Chrysler, as well as all Asian and European vehicles.



M500

M500

Hi-Tac Clamp for Domestic

M500 is ITS tested and certified for 5 ton pulling capacity. Comes with M50 L-shaped adapters. Dimensions 2-1/2" x 4-1/2"

Specifically for domestic automobiles including all General Motors, Chrysler and Ford Models.



PAICL0690

PAICL0690

Bite-Tite 3-ton Extended Nose Clamp

Extended nose for greater reach for those hard-to-reach pulls. Greater depth of teeth for additional gripping power.

Capacity: pull ring 3 tons (2.7 t), side pull adapter 3 tons (2.7 t)

Gripping Surface: 1-1/4" (32 mm) wide x 27/32" (21 mm) deep

Minimum Throat Clearance: 15/16" (23 mm)

Overall Length: 8" (203 mm)

Weight: 2-3/8 lbs. (1.1 kg)



PAICL1590

PAICL1590

Bite-Tite 6-ton Angle Clamp

Angled nose for those "angled" hard-to-pull applications.

Capacity: pull ring 6 tons (5.4 t), side pull adapter 4 tons (3.6 t)

Gripping Surface: 2-15/16" (74 mm) wide x 3/8" (9 mm) deep

Minimum Throat Clearance: 1-1/2" (38 mm)

Overall Length: 10-3/16" (259 mm)

Weight: 5-1/8 lbs. (2.4 kg)

PAICL1490



PAICL1490

Weld & Work Multi-Angle Swiveling Clamp

Versatile clamp. Designed for those hard and/or impossible to clamp and/or hold pulls. Pull ring utilizes a contoured dovetail channel that allows both multi-angle pulling for more "in-line" pulls and swiveling that minimizes chain twisting.

Specifications:

Capacity: 3 tons (2.7 t)

Overall Length: 9" (229 mm)

Weight: 3-1/4 lbs. (1.5 k)



HBA5



Portable systems—no dedicated bay required.

Bay space is a premium, a value your shop deserves.

Dollars saved is a daily return.

HBA5

Headlight Aimer

- Height: 68"
- Width: 26"
- Depth: 26"
- Weight: 85 Lbs.
- Power 9.6 v Rechargeable Battery with 110 v AC Adapter
- Depth: 13-5/8'
- Width: 17-11/16"
- Length: 66"



LCA 2EZ

Headlight Aimer

- Height: 58"
- Width: 26"
- Depth: 30"
- Weight: 71 lbs.
- Depth: 12"
- Width: 22"
- Length: 52"



LCA 2EZ