

GUN WASHERS

herkules™

Uni-ram



HERGW-SS

HERGW-SS Paint Gun Washer

Features:

- Cleans two guns and two cups simultaneously
- Filter/regulator
- 18-gauge stainless steel construction
- Automatic timer
- Extra large tank—17" long x 22" wide x 19" deep
- Diaphragm pumps
- Internal solvent reservoir
- FM approved
- Solvent or waterborne compatible
- Foot operated lid opener
- Safety lid shut-off switch
- Enclosed cabinet
- Reduces harmful V.O.C. emissions



HERG200

HERG200 Two Gun Washer with Timer

Cleans TWO guns in 90 seconds.

When a painter cleans paint guns manually, he uses approximately ten to fifteen minutes per job. If a painter cleans six times per day, valuable time is wasted!

Take a look at the following example:

- 10 minutes x 6 cleanings per day = 1 hour per day
- 1 hour per day x 5 days per week =
- 5 hours per week cleaning paint guns =
- 20 hours per month cleaning paint guns =
- 20 hours per month x 12 months =
- 240 hours per year cleaning paint guns =
- 240 hours per year x \$28.00 per hr bill out rate =

\$6,720 of lost bill out potential

You can easily see the savings one paint gun cleaner can give you and your shop, with THIS two gun washer, you can double your savings!

A paint gun washer will increase your profits within a very short period of time, get yours today and start saving!

HERO500 Gun Washer

Features:

- Cleans one gun and one cup simultaneously
- Industrial strength polyethylene tub
- Dual filter
- Automatic timer
- Diaphragm pump
- Safety lid shut-off switch
- Enclosed cabinet

HERO500



REDUCE HAZARDOUS WASTE

Re-using solvent means less hazardous waste disposal.

EXTRA LARGE TANK

Oversize tank—17" long x 22" wide x 25" deep—provides for easy set-up of guns, cups and sundries.

INTERNAL SOLVENT RESERVOIR

The diaphragm pump works effortlessly by drawing from below the internal solvent reservoir. This design ensures air-tight circulation that maximizes spray nozzle pressure.

INDUSTRIAL STRENGTH DIAPHRAGM PUMP

Herkules incorporates the most advanced American-made technology in all of its gun washers.

URCUG7500E CASCADE—Top of the Line with State-of-the-Art Manual Cleaning

- Cleans two Guns; two Pots
- 14 Jets
- Automatic Wash, Air Purge and Clean Rinse (100 cc) cycle
- Manual Wash and Manual Rinse using flow-through Brush
- Solvent Flow activated by "hands-free" foot pedal
- Vented Hood with manual override
- Work Surface
- Automatic Hose Cleaning with Wash Solvent, Air, Clean Solvent and Air again—all in less than 60 seconds
- New spigot and sink for convenient cleaning



URCUG7500E

URCCOMB05E75 Combination Unit of URCUG7500E and URCURS500EP2



URCCOMB05E40 Combination Spray Gun Cleaning with Automatic Solvent Recycling

Spray Gun Cleaner:

- Cleans two Paint Guns, two Pots
- 14 Swirl Action Jets
- Automatic Wash, Air Flush and Clean Rinse(100 cc) cycle.
- Manual rinse using pedal activated flow-through brush.
- Dual Diaphragm Pump
- Built-in Vent for automatic fume extraction
- Tank: 13" W x 17" D x 13" H



URCCOMB05E40

Automatic Solvent Recycler:

Powered by heavy-duty diaphragm pump, timer automatically transfers five gallons of dirty solvent into the recycler tank and a timer transfers clean solvent from the recycler. Includes five gallon pail and transfer hoses.

Display: LEDs indicates power on, heat on and six temperature set points.

Air Pressure: 75-85 PSI, unit complete with pressure regulator and filter.

Tank Capacity: 5.0 US gal. (20 litres)

Speed: 5 US gal. in about four hours

Solvent Transfer: Auto-transfer, In and Out

Power Supply: 110/120 V, 1,600 W, 13.3 A

Heater: 1,500 W

URCUG4000E CASCADE—The Automotive Spray Gun Cleaning System

- Cleans two Paint Guns, two Pots
- 14 Swirl Action Jets
- Automatic Wash, Air Flush and Clean Rinse (100 cc) cycle.
- Manual rinse using pedal activated flow-through brush.
- Dual Diaphragm Pump
- Built-in Vent for automatic fume extraction
- Tank: 13" W x 17" D x 13" H



URCUG4000E

URCURS500EP2 Automatic Solvent Recycler

Tank Capacity: 5.0 US gal. (20 litres)

Speed: 5 US gal. in about four hours

Solvent Transfer: Auto-transfer, In and Out

Powered by heavy-duty diaphragm pump, timer

automatically transfers five gallons of dirty solvent into the recycler tank and a timer transfers clean solvent from the recycler. Includes five gallon pail and transfer hoses.

Air Pressure: 75-85 PSI, unit complete with pressure regulator and filter.

Power Supply: 110/120 V, 1,600 W, 13.3 A

Heater: 1,500 W

Display: LEDs indicates power on, heat on and six temperature set points.



URCURS500EP2