

MATERIAL SAFETY DATA SHEET

DATE PRINTED: 5/19/2005
W M Barr

PAGE 1

SECTION 1. CHEMICAL PRODUCT AND COMPANY INFORMATION

MANUFACTURERS NAME: W.M. BARR & COMPANY, INC.
 ADDRESS: 2105 Channel Avenue, Memphis, TN 38113 USA
 EMERGENCY TELEPHONE #1: 901-775-0100
 EMERGENCY CONTACT: W.M. Barr Technical Services

EMERGENCY INFORMATION
 "3E" 24 HOUR MEDICAL EMERGENCY #, 800 451-8346.
 SEE SECTION 5 FOR ADDITIONAL EMERGENCY INFORMATION

INVENTORY ITEM #
 EFS459

PRODUCT NAME
 KS PEELER 18 OZ AERO

REVISED BY: W.M. Barr Technical Services
 REVISION DATE: 4/30/1999

SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS

SUBSTANCE DESCRIPTION	PERCENT	CAS#	CARCINOGENICITY			
			NTP	ACGIH	OSHA	IARC
METHYLENE CHLORIDE	70- 75	75-09-2	Y	Y	N	Y
PROPELLANT	20- 25	68476-85-7	N	N	N	N
** ABOVE INGREDIENT CONSISTS OF THE FOLLOWING **						
PROPANE	70- 75	74-98-6	N	N	N	N
BUTANE	15- 20	106-97-8	N	N	N	N
ISOBUTANE	10- 15	N/A	N	N	N	N
METHANOL	1- 5	67-56-1	N	N	N	N

SECTION 3. REGULATORY INFORMATION

EXPOSURE LIMITS/REGULATORY INFORMATION

SUBSTANCE DESCRIPTION	REG. AGENCY U/M		TWA	STEL	CEIL	SKIN	PEL
	ACGIH	OSHA					
METHYLENE CHLORIDE	ACGIH	PPM	50.00	N/E	N/E	N	N/E
	OSHA	PPM	25.00	125.00	1000.00	N	N/E

OSHA PEAK CONCENTRATION FOR 8HR SHIFT: 2000 PPM FOR 5 MIN. IN ANY 2 HRS.
 EMPLOYERS ARE REQUIRED TO CONDUCT INITIAL MONITORING OF AIRBORNE METHYLENE CHLORIDE, (MC), CONCENTRATIONS AND TO CONDUCT PERIODIC (MC) EXPOSURE MONITORING FOR ALL TASKS WHERE EMPLOYEE EXPOSURES ARE ABOVE ACTION LEVEL (12.5 PPM, 8-HR TWA) OR STEL. NTP-ANTICIPATED CARCINOGEN; IARC POSSIBLE CARCINOGEN (2B); ACGIH-SUSPECTED CARCINOGEN (A2); NIOSH-DEFINED CARCINOGEN. (MC) HAS CAUSED CANCER IN CERTAIN LABORATORY ANIMAL TESTS. RISK TO YOUR HEALTH DEPENDS ON LEVEL AND DURATION OF EXPOSURE.

PROPELLANT	ACGIH	PPM	N/E	N/E	N/E	N	N/E
	OSHA	PPM	N/E	N/E	N/E	N	N/E
PROPANE	ACGIH	PPM	N/E	N/E	N/E	N	N/E
	OSHA	PPM	1000.00	N/E	N/E	N	1000.00
BUTANE	ACGIH	PPM	800.00	N/E	N/E	N	N/E
	OSHA	PPM	800.00	N/E	N/E	N	N/E
ISOBUTANE	ACGIH	PPM	N/E	N/E	N/E	N	N/E
	OSHA	PPM	N/E	N/E	N/E	N	N/E

MATERIAL SAFETY DATA SHEET

DATE PRINTED: 5/19/2005
W M Baff

PAGE 2

SECTION 3. REGULATORY INFORMATION
(CONTINUED)

METHANOL	ACGIH	PPM	200.00	250.00	N/E	Y	N/E
	OSHA	PPM	200.00	250.00	N/E	Y	200.00

ADDITIONAL REGULATORY INFO

The time weighted average (TWA) value described herein is a threshold limit value (TLV) as established by ACGIH. The permissible exposure limit (PEL) is a value established by OSHA.

CALIFORNIA (PROPOSITION #65)

WARNING: Using this product will expose you to Methylene Chloride, which is known to cause cancer.

SEC. 313 SUPPLIER NOTIFICATION

The following information must be included in all MSDS that are copied and distributed for this material.

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40CFR 372):

SUBSTANCE DESCRIPTION	PERCENT BY WEIGHT (UPPER LIMIT)	CAS#
METHYLENE CHLORIDE	75	75-09-2
METHANOL	5	67-56-1

CLEAN AIR ACT

This formula contains no known ozone depleting chemicals.

HAZARD COMMUNICATION STANDARD

This document is prepared in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200). This MSDS contains thirteen (13) sections.

The following effects and/or symptoms are not expected to be experienced by persons who use this product properly and according to ALL instructions, precautions, and warnings; however, should the product user experience ANY questionable effects or symptoms, the product user should immediately seek medical attention.

SECTION 4. HAZARDS IDENTIFICATION

INHALATION ACUTE EXPOSURE EFFECTS

Vapor harmful. Harmful if inhaled. May cause dizziness; headache; irritation of the respiratory tract; nausea; numbness in fingers, arms and legs; hot flashes; depression of the central nervous system; spotted vision; dilation of pupils; increase in carboxy-hemoglobin levels which can cause stress to the cardiovascular system; vomiting; visual disturbances; giddiness and intoxication sleepiness; irregular or rapid heartbeat; convulsions; unconsciousness; and death. Elevated carboxyhemoglobin levels can be additive to the increase caused by smoking and other carbon monoxide sources.

SKIN CONTACT ACUTE EXPOSURE EFFECTS

This product is a skin irritant. Product may be absorbed through the skin if contact with skin is prolonged. May cause irritation; drying of skin; defatting and dermatitis. May increase severity of symptoms listed under inhalation. May cause additional symptoms listed under inhalation.

MATERIAL SAFETY DATA SHEET

DATE PRINTED: 5/19/2005
W M Baff

PAGE 3

SECTION 4. HAZARDS IDENTIFICATION
(CONTINUED)
-----**EYE CONTACT ACUTE EXPOSURE EFFECTS**

This material is an eye irritant. May cause irritation; burns; conjunctivitis of eyes; and corneal ulcerations of the eye. Vapors may also cause irritation.

INGESTION ACUTE EXPOSURE EFFECTS

Harmful if swallowed. May cause dizziness; headache; nausea; vomiting; stupor; irritation to mouth, throat and stomach; depression of the central nervous system; gastrointestinal irritation; diarrhea; narcosis; blindness; liver damage; kidney damage; heart damage and death. May produce additional symptoms listed under inhalation; Liquid aspirated into lungs, during vomiting, may cause chemical pneumonia and systemic effects.

CHRONIC EXPOSURE EFFECTS

Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. May cause skin irritation; permanent central nervous system changes; decreased response to visual and auditory stimulation; conjunctivitis; visual impairment or blindness; hallucinations; gastric disturbances; liver damage; blood disorders; pancreatic damage; kidney damage; and death. May cause additional symptoms listed under inhalation.

MEDICAL CONDITIONS AGGRAVATED

Diseases of the skin; eyes; blood; liver; kidneys; lungs; cardiovascular system; respiratory system; in addition to alcoholism; and rhythm disorders of the heart.

PRIMARY ROUTE OF EXPOSURE

Inhalation, ingestion, and dermal.

SECTION 5. FIRST AID MEASURES
-----**INHALATION**

If user experiences breathing difficulty, move to air free of vapors. Administer oxygen or artificial respiration until medical assistance can be rendered.

SKIN CONTACT

Wash with soap and water. Seek medical attention if irritation from contact persists.

EYE CONTACT

Immediately flush with water for at least 15 minutes. Get medical attention immediately.

INGESTION

Call your poison control center, hospital emergency room, or physician immediately for instructions.

NOTE TO PHYSICIAN

THIS PRODUCT CONTAINS METHYLENE CHLORIDE AND LESS THAN 4% METHANOL. Methanol is metabolized to formaldehyde and formic acid. These metabolites may cause metabolic acidosis, visual disturbances, and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion. Ethanol competes for the same metabolic pathway and has been used as an antidote. Methanol is effectively removed by hemodialysis. Adrenalin should never be given to a person overexposed to methylene chloride. This formula is registered with POISINDEX. Call your local poison control center for further information.

MATERIAL SAFETY DATA SHEET

DATE PRINTED: 5/19/2005
W M Baff

PAGE 4

SECTION 6. FIRE FIGHTING MEASURES

HAZARD RATING SOURCE	HMIS	NFPA
HEALTH	2	2
FLAMMABILITY	4	4
REACTIVITY	0	0
OTHER	G	NA

FLASH METHOD
FLAME EXTENSIONFLASH POINT
N/E F N/E C NOT APPLICABLELOWER EXPLOSION LIMIT
1.8

GENERAL COMMENTS

Aerosol Flammability Classification according to ASTM D-3065-77 and FHSA 1500.45.

CPSC FLAMMABILITY: Flammable Aerosol

EXTINGUISHING METHOD

Use carbon dioxide, dry powder, or foam.

FIRE FIGHTING PROCEDURES

Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.

FIRE AND EXPLOSION HAZARDS

DANGER! FLAMMABLE. KEEP AWAY FROM HEAT, SPARKS, FLAME, AND ALL OTHER SOURCES OF IGNITION. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and all other sources of ignition during use and until all vapors are gone. Beware of static electricity that may be generated by synthetic clothing and other sources. Contact with flames may generate toxic fumes. Contents under pressure. Do not puncture, incinerate or store above 120 degrees F. Exposure to heat or prolonged exposure to sun may cause bursting.

SECTION 7. ACCIDENTAL RELEASE MEASURES

CLEAN-UP

Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area. SMALL SPILLS: take up liquid with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable. LARGE SPILLS: dike far ahead of spill for later disposal.

For transportation related spills contact Chemtrec at 1-800-424-9300 for emergency assistance.

WASTE DISPOSAL

Dispose in accordance with applicable local, state and federal regulations.

MATERIAL SAFETY DATA SHEET

DATE PRINTED: 5/19/2005
W M Barr

PAGE 5

SECTION 8. HANDLING AND STORAGE
-----**STORAGE**

Store as Level 1 Aerosol (NFPA 30B)
Replace overcap on container after each use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.

HANDLING

Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

SECTION 9. TRANSPORT INFORMATION
-----**TRANSPORTATION**

For D.O.T. information, contact W.M. Barr Technical Services Department.

SECTION 10. EXPOSURE CONTROLS/PERSONAL PROTECTION
-----**VENTILATION PROTECTION**

Use only with adequate ventilation to prevent build-up of vapors. Open all windows and doors. Use only with a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea, or eye-watering - STOP - ventilation is inadequate. Leave area immediately.

RESPIRATORY PROTECTION

For OSHA controlled work place and other regular users - Use only with adequate ventilation under engineered air control systems designed to prevent exceeding appropriate TLV. For occasional use, where engineered air control is not feasible, use properly maintained and properly fitted NIOSH approved self-contained breathing apparatus for chlorinated solvent vapors. A dust mask does not provide protection against vapors.

SKIN PROTECTION

Wear impermeable gloves. Gloves contaminated with product should be discarded. Promptly remove clothing that becomes soiled with product.

EYE PROTECTION

Safety glasses, chemical goggles or face shields are recommended to safeguard against potential eye contact, irritation, or injury. Contact lenses should not be worn while working with chemicals.

OTHER PROTECTION

Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure. A source of clean water should be available in the work area for flushing eyes and skin. Do not eat, drink, or smoke in the work area. Wash hands thoroughly after use. Before reuse, thoroughly clean any clothing or protective equipment that has been contaminated by prior use. Discard any clothing or other protective equipment that cannot be decontaminated, such as gloves or shoes.

SECTION 11. PHYSICAL AND CHEMICAL PROPERTIES
-----**VOLATILE %**
97.44

MATERIAL SAFETY DATA SHEET

DATE PRINTED: 5/19/2005
W M Baff

PAGE 6

SECTION 11. PHYSICAL AND CHEMICAL PROPERTIES
(CONTINUED)
-----**BOILING POINT**

GT 104.00 F 40.00 C BOILING RANGE 104 F - 148 F

VAPOR DENSITY (Air = 1.0)
HEAVIER THAN AIR**EVAPORATION RATE**
SLOWER THAN ETHER**BULK DENSITY**
10.640
LB/GAL**pH FACTOR**
N/E**PHOTOCHEMICALLY REACTIVE**
NO**MAX V.O.C.**
29 % by weight**MAX VAPOR PRESSURE**
(of the V.O.C.) 10mm Hg at 20 degrees C
-----SECTION 12. STABILITY AND REACTIVITY
-----**INCOMPATIBILITIES**

Incompatible with strong oxidizing agents; strong caustics; acids; alkalis; oxygen; nitrogen peroxide; chemically active metals such as aluminum and magnesium; sodium, and potassium; reducing agents; and nitric acid.

DECOMPOSITION

Thermal decomposition may produce carbon monoxide; carbon dioxide; small quantities of phosgene; chlorine gas; formaldehyde; hydrogen chloride; and unidentified organic compounds in black smoke.

POLYMERIZATION

Will not occur.

STABILITYStable.
-----SECTION 13. ADDITIONAL INFORMATION
-----**IMPORTANT NOTE**

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

LEGEND:PPM = parts per million
MG/M3 = milligrams per cubic meter
N/E or NE = none established
GT = greater than

MATERIAL SAFETY DATA SHEET

DATE PRINTED: 5/19/2005
W M Baff

PAGE 7

SECTION 13. ADDITIONAL INFORMATION
(CONTINUED)

N/A or NA = not applicable
TCC = tag closed cup
TOC = tag open cup
PMCC = Pensky-Martens closed cup
IDLH = Immediately Dangerous to Life and Health

END OF MSDS